



Project Reference: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Cat. No: \_\_\_\_\_ Voltage: \_\_\_\_\_ Finish: \_\_\_\_\_

**MICRON** 1-lamp, 2-lamp, 3-lamp recessed 2X2, 2X4 and 1X4  
high performance direct-indirect commercial / retail

T8, T5, T5/HO, PLL + Instant Start or Rapid Start electronic ballast CSA, UL or equivalent

IP40



9020-3PL  
9020-2PL  
9020-1PL



9040-2F32  
9040-3F32



9022-2F32  
9022-2F54

**ORDERING INFORMATION**

Catalog No.	Lamps		Nom. Size
9020-2PL40	(2) PLL40	<b>2X2</b>	24" x 24" x 4"
9020-3PL40	(3) PLL40		24" x 24" x 4"
9020-2PL55	(2) PLL55		24" x 24" x 4"
9040-2F32	(2) F32 T8	<b>2X4</b>	24" x 48" x 4"
9040-3F32	(3) F32 T8		24" x 48" x 4"
9040-2F28	(2) F28 T5		24" x 48" x 4"
9040-1F54	(1) F54 T5 HO		24" x 48" x 4"
9040-2F54	(2) F54 T5 HO		24" x 48" x 4"
9040-3F54	(3) F54 T5 HO		24" x 48" x 4"
9022-2F32	(2) F32 T8	<b>1X4</b>	12" x 48" x 4"
9022-1F32	(1) F32 T8		12" x 48" x 4"
9022-2F28	(2) F28 T5		12" x 48" x 4"
9022-1F54	(1) F54 T5 HO		12" x 48" x 4"
9022-2F54	(2) F54 T5 HO		12" x 48" x 4"

**AVAILABLE OPTIONS**

HIGH BALLAST FACTOR BALLAST (T8): Suffix -HBF

HI-LO ENERGY SAVING - remote switching or motion sensor - Suffix -HL

EMERGENCY BALLAST - - Suffix -EB

In 2007 Valuelight designed the new SemiTrans™ high performance, high efficiency optical system with high translucency lamp shielding film inserted in the optical shield - "wire mesh basket".

Micron luminaries with SemiTrans™ provide the perfect blend of efficiency, glare control, space brightness and light control - making people more satisfied and productive within a healthier environment. By increasing comfortable indirect brightness throughout the space, Micron fixtures deliver lighting with soft shadows and reduced contrast creating brighter space that is visually very comfortable. Attractive design blends well with all popular ceiling systems. Drywall mounting kits and surface / suspended trim kits are available. Contact Valuelight for details.

- Hi-Lo will not affect appearance in Low mode
- heavy gauge steel housing
- powder coated ultra bright white
- electronic ballast
- 120V, 120-277V, 347V/60 Hz and 220-240V/50Hz
- polycarbonate lamp holders
- max. six years fixture warranty

Specifications are subject to change without notice

**QUESTIONS?** Please call customer service at 1-800-49-LAMPS (800-495-2677) or contact your local VALUELIGHT representative