


Architectural downlighting

SYNERGY 6 horizontal

energy efficient



7-3/8"

4-1/4"



2 x PLC 26W max.



Ø 6-1/2"



State - Of - The - Art Illumination

Explore the Synergy value for yourself!

Energy Efficient, Cool Operating

Low energy recessed luminaries that have combined the requirements of energy efficiency with premium light output from the latest compact fluorescent lamps and advances in the use of integrated high frequency electronic ballasts.

Architectural Six Inch Aperture

Smaller 6" aperture delivers architecturally clean appearance with no compromise to performance or efficiency.

High Performance Optical System

CAD optimized, multi-parabolic anodized low iridescence aluminum reflector provides highest efficiency possible.

One Size Fits All

With uniform aperture size specified through the entire range of Synergy luminaries, now you have an opportunity to easily combine all available lamping options.

Lumen Output

2 x 13W Initial Lumens: 1800

2 x 18W Initial Lumens: 2500

2 x 26W Initial Lumens: 3600

Standard Ballast:

Solid State Electronic Ballast

- High Performance
- High Power Factor
- Five Year Warranty

Available Voltages:

Identify by proper suffix:

- .120V 60 Hz
- .240V 50 / 60 Hz
- .277V 60 Hz
- .347V 60 Hz



PRODUCT CODE	FIXTURE DESCRIPTION	LAMP	LAMPS	LAMPS	Ø APERTURE	Ø O. D.	WARRANTY
3077.213.120	SYNERGY HORIZONTAL	COMP. FLUOR.	2 x 13W	PL	6"	7 - 3/8"	5 Years
3077.218.120	SYNERGY HORIZONTAL	COMP. FLUOR.	2 x 18W	PLC	6"	7 - 3/8"	5 Years
3077.226.120	SYNERGY HORIZONTAL	COMP. FLUOR.	2 x 26W	PLC	6"	7 - 3/8"	5 Years

Available with New Construction Housing for pre-drywall installations only.

✓ **Five year warranty includes electronic ballast.**

Due to constant product upgrading and refinement, specifications are subject to change without notice.



valuelight.com

practical ideas
you need to
design specify
superior
lighting systems